MODEL TS 4500P

TECHNICAL SPECIFICATION

LOA	4.5M
BEAM	2.0M
DRAFT	0.41M
HULL WEIGHT	430 kg
PERSONS	6
MAX ENGINE	60 HP
REC. ENGINE	FROM 40HP
MAX LOAD	700KG
TRANSOM	L TYPE
DEADRICE	22 degree
FUEL TANK	35 L





Standard scope of supply:

- 1 Hull Material HDPE (black colour)
- 2 Fender 10 mm HDPE (red colour UV resistance)
- 3 Foam filling inside of the half tube 400mm
- 4 Compartments in tube structure splitted by bulkheads
- 5 Self-drainage deck 2 outlets D 50mm in transom
- 6 Drinage plug in transom D25 mm from DB
- 7 Tunnel in the DB for laying control systems D75mm-1 pcs
- 8 Inspection hatch D 190mm for engine bolts installation 1pcs
- 9 Drinage plugs d 25 mm in technical compartmets 2 pcs
- 10 Fuel tank 35 L installed on deck -1 pcs
- 11 Fuel compartment ventilation system
- 12 Reinforced transom by AL angle bar 130x65
- 13 Mooring places (Ducks) 4 pcs
- 14 Storage compartment + door in front 1pcs
- 15 Non-slip rubber mat on the deck (removable)
- 16 Center Console + Access Hatch 1pcs
- 17 Battery holder in Aft storage compartment x 1 pcs
- 18 Manual Bilge pump from DB (35L per min)
- 19 Safety rope around boat D18 mm (Navyblue)
- 20 Technical storage in AFT with hatches 2 pcs
- 21 Step platform with anti slip cnc methhod 1pcs
- 22 CE certification, category C

- 23 Storage compartment in AFT 3pcs
- 24 Lockers for storage hatch (Roca) 6pcs
- 25 Hatch holder stainless steel 3 pcs
- 26 Soft seats on Aft storage compartment t=50 mm 3 pcs

Options:

- 1 Storage box on deck 400x400
- 2 A-frame in AFT for navigation light,etc (Stainless steel)
- 3 Permanently installed bigger fuel tank under the deck
- 4 Top light
- 5 Navigation ligtsight
- 6 Main switch installed to Center console (Bluesea) -1 pcs
- 7 Switch panel for nav. lights + reserve (total 4 pcs Bluesea)
- 8 Other type of console

