

MODEL TS 5900

TECHNICAL SPECIFICATION

LOA	5.9M
BEAM	2.3M
DRAFT	0.45M
HULL WEIGHT	850 kg
PERSONS	8
MAX ENGINE	115 HP
REC. ENGINE	FROM 70HP
MAX LOAD	1000KG
TRANSOM	UL TYPE
DEADRICE	22 degree
FUEL TANK	130 L



Standard scope of supply:

- 1 Hull Material HDPE (black colour)
- 2 Fender 10 mm HDPE (red colour UV resistance)
- 3 Foam filling inside of the 500mm tube
- 4 Compartments in tube structure splitted by bulkheads
- 5 Self-drainage deck – 2 outlets D 50mm in transom
- 6 Drainage plug in transom D25 mm from DB
- 7 Tunnel in the DB for laying control systems D75mm– 2 pcs
- 8 Towing points in AFT – 2pcs
- 9 Inspection hatch D 190mm for Fuel tank -1 pcs
- 10 Inspection hatch D 190mm for engine bolts installation - 1pcs
- 11 Drainage plugs d 25 mm in technical compartmets - 2 pcs
- 12 Drainage plug d 25 mm from Fuel compartment - 1 pcs
- 13 Fuel tank 130 L installed in DB -1 pcs
- 14 Fuel inlet D 50 mm in aft - 1 pcs
- 15 Fuel tank ventilation system
- 16 Fuel compartment ventilation system
- 17 Reinforced transom by AL angle bar 130x65
- 18 Mooring places (Ducks) – 4 pcs
- 19 Lifting pad eyes – 4 pcs
- 20 Storage compartment in AFT - 3pcs
- 21 Lockers for storage hatch (Roca) - 6pcs
- 22 Hatch holder stainless steel - 3 pcs
- 23 Storage compartment + door in front - 1pcs
- 24 Technical storage in AFT with hatches - 2 pcs
- 25 Steps in AFT with anti slip cnc method – 2 pcs
- 26 Step platform with anti slip cnc methhodo – 1pcs
- 27 Seats place on boards L 2000x 230 mm - 2pcs
- 28 Soft seats on Aft storage compartment t=50 mm - 3 pcs
- 29 Non-slip rubber mat on the deck (removable)
- 30 Center Console + Access Hatch - 1pcs
- 31 Windshield for console with SS railing - 1pcs
- 32 Main switch installed to Center console (Blueseas) -1 pcs
- 33 Switch panel for nav. lights + reserve (total 4 pcs Blueseas)
- 34 Battery holder under the console x 2 pcs
- 35 Manual Bilge pump from DB (35L per min)
- 36 Safety rope around boat D18 mm (Navyblue)
- 37 A-frame in AFT for navigation light, etc (Stainless steel)
- 38 Bow railings (Stainless steel)
- 39 Top light
- 40 Fuel separator outside box
- 41 Ultraflex Hose Through Bulkhead for hydraulic steering
- 42 CE certification, category C