MODEL TS 6400

TECHNICAL SPECIFICATION

LOA	6.4M
BEAM	2.3M
DRAFT	0.45M
HULL WEIGHT	960 kg
PERSONS	10
MAX ENGINE	150 HP
REC. ENGINE	FROM 100HP
MAX LOAD	1200KG
TRANSOM	UL TYPE
DEADRICE	22 degree
FUEL TANK	130 L





Standard scope of supply:

- 1 Hull Material HDPE (black colour)
- 2 Fender 10 mm HDPE (red colour UV resistance)
- 3 Foam filling inside of the 500mm tube
- 4 Compartments in tube structure splitted by bulkheads
- 5 Self-drainage deck 2 outlets D 50mm in transom
- 6 Drinage plug in transom D25 mm from DB
- 7 Tunnel in the DB for laying control systems D75mm-2 pcs
- 8 Towing points in AFT 2pcs
- 9 Inspection hatch D 190mm for Fuel tank -1 pcs
- 10 Inspection hatch D 190mm for engine bolts installation 1pcs
- 11 Drinage plugs d 25 mm in technical compartmets 2 pcs
- 12 Drinage plug d 25 mm from Fuel compartment 1 pcs
- 13 Fuel tank 130 L installed in DB -1 pcs
- 14 Fuel inlet D 50 mm in aft 1 pcs
- 15 Fuel tank ventilation system
- 16 Fuel compartment ventilation system
- 17 Reinforced transom by AL angle bar 130x65
- 18 Mooring places (Ducks) 4 pcs
- 19 Lifting pad eyes 4 pcs
- 20 Storage compartment in AFT 3pcs
- 21 Lockers for storage hatch (Roca) 6pcs
- 22 Hatch holder stainless steel 3 pcs

- 23 Storage compartment + door in front 1pcs
- 24 Technical storage in AFT with hatches 2 pcs
- 25 Steps in AFT with anti slip cnc method 2 pcs
- 26 Step platform with anti slip cnc methhod 1pcs
- 27 Seats place on boards L 2000x 230 mm 2pcs
- 28 Soft seats on Aft storage compartment t=50 mm 3 pcs
- 29 Non-slip rubber mat on the deck (removable)
- 30 Center Console + Access Hatch 1pcs
- 31 Windshield for console with SS railing 1pcs
- 32 Main switch installed to Center console (Bluesea) -1 pcs
- 33 Switch panel for nav. lights + reserve (total 4 pcs Bluesea)
- 34 Battery holder under the console x 2 pcs
- 35 Manual Bilge pump from DB (35L per min)
- 36 Safety rope around boat D18 mm (Navyblue)
- 37 A-frame in AFT for navigation light,etc (Stainless steel)
- 38 Bow railings (Stainless steel)
- 39 Navigation ligtsight
- 40 Top light
- 41 Fuel separator outside box
- 42 Ultraflex Hose Through Bulkhead for hydraulic steering
- 43 CE certification, category C

